

8-Bit Dual Supply Configurable Voltage Interface Transceiver


with 3-STATE Outputs

74LVXC3245

The LVXC3245 is a 24-pin dual-supply, 8-bit configurable voltage interface transceiver suited for PCMCIA and other real time configurable I/O applications. The V_{CCA} pin accepts a 3 V supply level. The A Port is a dedicated 3 V port. The V_{CCB} pin accepts a 3 V-to-5 V supply level. The B Port is configured to track the V_{CCB} supply level respectively. A 5 V level on the V_{CC} pin will configure the I/O pins at a 5 V level and a 3 V V_{CC} will configure the I/O pins at a 3 V level. The A Port should interface with a 3 V host system and the B Port to the card slots. This device will allow the V_{CCB} voltage source pin and I/O pins on the B Port to float when $\overline{OE}$ is HIGH. This feature is necessary to buffer data to and from a PCMCIA socket that permits PCMCIA cards to be inserted and removed during normal operation.


Features

- Bidirectional Interface Between 3.0 V and 3 V-to-5 V Buses
- Control Inputs Compatible with TTL Level
- Outputs Source/Sink Up to 24 mA
- Guaranteed Simultaneous Switching Noise Level and Dynamic Threshold Performance
- Implements Proprietary EMI Reduction Circuitry
- Flexible V_{CCB} Operating Range
- Allows B Port and V_{CCB} to Float Simultaneously When $\overline{OE}$ is HIGH
- Functionally Compatible With the 74 Series 245
- These Devices are Pb-Free and are RoHS Compliant



TSSOP24
CASE 948AR

MARKING DIAGRAMS



LVXC3245 = Specific Device Code
A = Assembly Location
WL, L = Wafer Lot
Y = Year
WW, W = Work Week
G = Pb-Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 7 of this data sheet.

74LVXC3245




Figure 1. Logic Symbol/s

PIN DESCRIPTIONS

Pin Names	Description
$\overline{OE}$	Output Enable Input
T/R	Transmit / Receive Input
A ₀ – A ₇	Side A Inputs or 3-STATE Outputs
B ₀ – B ₇	Side B Inputs or 3-STATE Outputs

TRUTH TABLE/s

Inputs		Outputs
$\overline{OE}$	T/R	
L	L	Bus B Data to Bus A
L	H	Bus A Data to Bus B
H	X	HIGH-Z State

H = HIGH Voltage Level
L = LOW Voltage Level
X = Immaterial




Figure 2. Connection Diagram/s




Figure 3. Logic Diagram

ABSOLUTE MAXIMUM RATINGS (Note 1)

Symbol	Parameter	Value	Condition	Unit
V_{CCA}, V_{CCB}	Supply Voltage	-0.5 to +6.5		V
V_I	DC Input Voltage $\overline{OE}, T/R$	-0.5 to $V_{CCA} + 0.5$		V
$V_{I/O}$	DC Input/Output Voltage An	-0.5 to $V_{CCA} + 0.5$		V
		Bn	-0.5 to $V_{CCB} + 0.5$	V
I_{IK}	DC Input Diode Current $\overline{OE}, T/R$	± 20		mA
I_{OK}	DC Output Diode Current	± 50		mA
I_O	DC Output Source or Sink Current	± 50		mA
I_{CC}, I_{GND}	DC V_{CC} or Ground Current Per Output Pin Max Current	± 50 ± 200		mA
T_{STG}	Storage Temperature Range	-65 to +150		°C
	DC Latch-Up Source or Sink Current	± 100		mA

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

RECOMMENDED OPERATING CONDITIONS (Note 2)

Symbol	Parameter	Min	Max	Unit
V_{CCA}, V_{CCB}	Supply Voltage V_{CCA} V_{CCB}	2.7 3.0	3.6 5.5	V
V_I	Input Voltage $\overline{OE}, T/R$	0	V_{CCA}	V
$V_{I/O}$	Input/Output Voltage An Bn	0 0	V_{CCA} V_{CCB}	V
T_A	Free-Air Operating Temperature	-40	+85	°C
$\Delta t/\Delta V$	Minimum Input Edge Rate V_{IN} from 30% to 70% of V_{CC} ; V_{CC} at 3.0 V, 4.5 V, 5.5 V	0	8	ns/V

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

1. The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.
2. The A Port unused pins (inputs or I/Os) must be held HIGH or LOW. They may not float.



DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter		Condition	V _{CCA}	V _{CCB}	T _A = 25 °C		T _A = -40 to +85 °C		Unit
						Typ	Guaranteed Limits			
V _{IHA}	Minimum HIGH Level Input Voltage	An OE T/R	V _{OUT} ≤ 0.1 V or ≥ V _{CC} - 0.1 V	2.7 3.0 3.6	3.0 3.6 5.5		2.0 2.0 2.0	2.0 2.0 2.0	V	
V _{IHB}		Bn		2.7 3.0 3.6	3.0 3.6 5.5		2.00 2.00 3.85	2.00 2.00 3.85	V	
V _{ILA}	Maximum LOW Level Input Voltage	An OE T/R	V _{OUT} ≤ 0.1 V or ≥ V _{CC} - 0.1 V	2.7 3.0 3.6	3.0 3.6 5.5		0.8 0.8 0.8	0.8 0.8 0.8	V	
V _{ILB}		Bn		2.7 3.0 3.6	3.0 3.6 5.5		0.80 0.80 1.65	0.80 0.80 1.65	V	
V _{OHA}	Minimum HIGH Level Output Voltage		I _{OUT} = -100 μA	3.0	3.0	2.99	2.90	2.90	V	
I _{OH} = -12 mA			3.0	3.0	2.85	2.56	2.46			
I _{OH} = -24 mA			3.0	3.0	2.65	2.35	2.25			
I _{OH} = -12 mA			2.7	3.0	2.50	2.30	2.20			
I _{OH} = -24 mA			2.7	4.5	2.30	2.10	2.00			
V _{OHB}			I _{OUT} = -100 μA	3.0	3.0	2.99	2.90	2.90	V	
I _{OH} = -12 mA			3.0	3.0	2.85	2.56	2.46			
I _{OH} = -24 mA			3.0	3.0	2.65	2.35	2.25			
I _{OH} = -12 mA			2.7	3.0	2.50	2.30	2.20			
I _{OH} = -24 mA			2.7	4.5	2.30	2.10	2.00			
V _{OLA}	Maximum LOW Level Output Voltage		I _{OUT} = 100 μA	3.0	3.0	0.002	0.10	0.10	V	
I _{OL} = 24 mA			3.0	3.0	0.21	0.36	0.44			
I _{OL} = 12 mA			2.7	3.0	0.11	0.36	0.44			
I _{OL} = 24 mA			2.7	4.5	0.22	0.42	0.50			
V _{OLB}			I _{OUT} = 100 μA	3.0	3.0	0.002	0.10	0.10	V	
I _{OL} = 24 mA			3.0	3.0	0.21	0.36	0.44			
I _{OL} = 12 mA			2.7	3.0	0.11	0.36	0.44			
I _{OL} = 24 mA			2.7	4.5	0.22	0.42	0.50			
I _{IN}	Maximum Input Leakage Current	OE, T/R	V _I = V _{CCA} , GND	3.6 3.6	3.6 5.5		±0.1 ±0.1	±1.0 ±1.0	μA	
I _{OZA}	Maximum 3-State Output Leakage	An	V _I = V _{IL} , V _{IH} OE = V _{CCA} V _O = V _{CCA} , GND	3.6 3.6	3.6 5.5		±0.5 ±0.5	±5.0 ±5.0	μA	
I _{OZB}	Maximum 3-State Output Leakage	Bn	V _I = V _{IL} , V _{IH} OE = V _{CCA} V _O = V _{CCB} , GND	3.6 3.6	3.6 5.5		±0.5 ±0.5	±5.0 ±5.0	μA	
ΔI _{CC}	Maximum I _{CC} /Input	Bn	V _I = V _{CCB} -2.1 V	3.6	5.5	1.0	1.35	1.5	mA	
		All Inputs	V _I = V _{CC} -0.6 V	3.6	3.6		0.35	0.5	mA	
I _{CCA1}	Quiescent V _{CCA} Supply Current as B Port Floats		An = V _{CCA} or GND Bn = Open, OE = V _{CCA} , T/R = V _{CCA} , V _{CCB} = Open	3.6	Open		5	50	μA	
I _{CCA2}	Quiescent V _{CCA} Supply Current		An = V _{CCA} or GND Bn = V _{CCB} or GND, OE = GND, T/R = GND	3.6 3.6	3.6 5.5		5 5	50 50	μA	
I _{CCB}	Quiescent V _{CCB} Supply Current		An = V _{CCA} or GND Bn = V _{CCB} or GND, OE = GND, T/R = V _{CCA}	3.6 3.6	3.6 5.5		5 8	50 80	μA	



NOISE CHARACTERISTICS

Symbol	Parameter	Condition	V _{CCA}	V _{CCB}	T _A = 25 °C		Unit
					Typ	Limit	
V _{OLPA}	Quiet Output Maximum Dynamic V _{OL}	(Note 3), (Note 4)	3.3 3.3	3.3 5.0		0.8 0.8	V
V _{OLPB}		(Note 3), (Note 4)	3.3 3.3	3.3 5.0		0.8 1.5	V
V _{OLVA}	Quiet Output Minimum Dynamic V _{OL}	(Note 3), (Note 4)	3.3 3.3	3.3 5.0		-0.8 -0.8	V
V _{OLVB}		(Note 3), (Note 4)	3.3 3.3	3.3 5.0		-0.8 -1.2	V
V _{IHDA}	Minimum HIGH Level Dynamic Input Voltage	(Note 3), (Note 5)	3.3 3.3	3.3 5.0		2.0 2.0	V
V _{IHDB}		(Note 3), (Note 5)	3.3 3.3	3.3 5.0		2.0 3.5	V
V _{ILDA}	Maximum LOW Level Dynamic Input Voltage	(Note 3), (Note 5)	3.3 3.3	3.3 5.0		0.8 0.8	V
V _{ILDB}		(Note 3), (Note 5)	3.3 3.3	3.3 5.0		0.8 1.5	V

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Worst case package.

4. Max number of outputs defined as (n). Data inputs are driven 0 V to V_{CC} level; one output at GND.

5. Max number of data inputs (n) switching. (n-1) inputs switching 0 V to V_{CC} level. Input under test switching: V_{CC} level to threshold (V_{IHD}), 0 V to threshold (V_{ILD}), f = 1 MHz.

AC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	T _A = +25 °C; C _L = 50 pF V _{CCA} = 2.7-3.6 V V _{CCB} = 4.5-5.5 V			T _A = -40 °C to +85 °C; C _L = 50 pF V _{CCA} = 2.7-3.6 V V _{CCB} = 4.5-5.5 V		T _A = +25 °C; C _L = 50 pF V _{CCA} = 2.7-3.6 V V _{CCB} = 3.0-3.6 V			T _A = -40 °C to +85 °C; C _L = 50 pF V _{CCA} = 2.7-3.6 V V _{CCB} = 3.0-3.6 V		Unit
		Min	Typ (Note 6)	Max	Min	Max	Min	Typ (Note 7)	Max	Min	Max	
t _{PHL} t _{PLH}	Propagation Delay A to B	1.0 1.0	4.8 3.9	8.0 6.5	1.0 1.0	8.5 7.0	1.0 1.0	5.5 5.2	8.5 8.0	1.0 1.0	9.0 8.5	ns
t _{PHL} t _{PLH}	Propagation Delay B to A	1.0 1.0	3.8 4.3	6.5 7.5	1.0 1.0	7.0 8.0	1.0 1.0	4.4 5.1	7.0 7.5	1.0 1.0	7.5 8.0	ns
t _{PZL} t _{PZH}	Output Enable Time OE to B	1.0 1.0	4.7 4.8	8.0 8.5	1.0 1.0	8.5 9.0	1.0 1.0	6.0 6.1	9.0 9.5	1.0 1.0	9.5 10.0	ns
t _{PZL} t _{PZH}	Output Enable Time OE to A	1.0 1.0	5.9 5.4	9.5 9.0	1.0 1.0	10.0 9.5	1.0 1.0	6.4 5.8	10.0 9.0	1.0 1.0	10.5 9.5	ns
t _{PHZ} t _{PLZ}	Output Disable Time OE to B	1.0 1.0	4.0 3.8	8.0 7.5	1.0 1.0	8.5 8.0	1.0 1.0	6.3 4.5	9.5 8.5	1.0 1.0	10.0 8.5	ns
t _{PHZ} t _{PLZ}	Output Disable Time OE to A	1.0 1.0	4.6 3.1	9.5 6.5	1.0 1.0	10.0 7.0	1.0 1.0	5.2 3.4	9.5 6.5	1.0 1.0	10.0 7.0	ns
t _{OSSL} t _{OSLH}	Output to Output Skew, (Note 8) Data to Output		1.0	1.5		1.5		1.0	1.5		1.5	ns

6. Typical values at V_{CCA} = 3.3 V, V_{CCB} = 5.0 V at 25 °C.

7. Typical values at V_{CCA} = 3.3 V, V_{CCB} = 3.3 V at 25 °C.

8. Skew is defined as the absolute value of the difference between the actual propagation delay for any two separate outputs of the same device. The specification applies to any outputs switching in the same direction, either HIGH-to-LOW (t_{OSSL}) or LOW-to-HIGH (t_{OSLH}); parameter guaranteed by design.



CAPACITANCE

Symbol	Parameter	Condition	Typical	Unit
C_{IN}	Input Capacitance	$V_{CC} = \text{Open}$	4.5	pF
$C_{I/O}$	Input/Output Capacitance	$V_{CCA} = 3.3 \text{ V}; V_{CCB} = 5.0 \text{ V}$	10	pF
C_{PD}	Power Dissipation Capacitance (Measured at 10 MHz)	$V_{CCB} = 5.0 \text{ V}$ $V_{CCA} = 3.3 \text{ V}$	50 40	pF

Power Up Considerations

To insure the system does not experience unnecessary I_{CC} current draw, bus contention, or oscillations during power up, the following guidelines should be adhered to (refer to Table 1):

- Power up the control side of the device first. This is the V_{CCA} side.
- $\overline{OE}$ should ramp with or ahead of V_{CCA} . This will help guard against bus contention.
- The Transmit/Receive control pin ($T/\overline{R}$) should ramp with V_{CCA} , this will ensure that the A Port data pins are

configured as inputs. With V_{CCA} receiving power first, the A I/O Port should be configured as inputs to help guard against bus contention and oscillations.

- A side data inputs should be driven to a valid logic level. This will prevent excessive current draw.

The above steps will ensure that no bus contention or oscillations, and therefore no excessive current draw occurs during the power up cycling of these devices. These steps will help prevent possible damage to the translator devices and potential damage to other system components.

Table 1. Low Voltage Translator Power Up Sequencing Table

Device Type	V_{CCA}	V_{CCB}	$T/\overline{R}$	$\overline{OE}$	A Side I/O	B Side I/O	Floatable Pin Allowed
74LVXC3245	3 V (power up 1st)	3 V to 5.5 V configurable	ramp with V_{CCA}	ramp with V_{CCA}	logic 0 V or V_{CCA}	outputs	yes, V_{CCB} and B I/O's w/ $\overline{OE}$ HIGH

Please reference Application Note [AN-5001](#) for more detailed information on using onsemi's LVX Low Voltage Dual Supply CMOS Translating Transceivers.



74LVXC3245

Configurable I/O Application for PCMCIA Cards




Figure 4. Block Diagram

The LVXC3245 is a 24-pin dual supply device well suited for PCMCIA configurable I/O applications. Ideal for low power notebook designs, the LVXC3245 consumes less than 1 mW of quiescent power in all modes of operation. The LVXC3245 meets all PCMCIA I/O voltage requirements at 5 V and 3.3 V operation. By tying V_{CCB} of the LVXC3245 to the card voltage supply, the PCMCIA card will always experience rail to rail output swings, maximizing the reliability of the interface.

The V_{CCA} pin on the LVXC3245 must always be tied to a 3 V power supply. This voltage connection provides internal references needed to account for variations in V_{CCB} . When connected as in the figure above, the LVXC3245 meets all the voltage and current requirements of the ISA bus standard (IEEE P996).

ORDERING INFORMATION

Device	Package	Shipping [†]
74LVXC3245MTCX	TSSOP-24 (Pb-Free)	2500 Tape & Reel

[†] For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, [BRD8011/D](#).

REVISION HISTORY


Revision	Description of Changes	Date
2	Converted the Data Sheet to onsemi format.	9/16/2025

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.





TSSOP24, 4.4x7.8
CASE 948AR
ISSUE A

DATE 17 MAR 2009



SYMBOL	MIN	NOM	MAX
A			1.20
A1	0.05		0.15
A2	0.80		1.05
b	0.19		0.30
c	0.09		0.20
D	7.70	7.80	7.90
E	6.25	6.40	6.55
E1	4.30	4.40	4.50
e	0.65 BSC		
L	0.50	0.60	0.70
L1	1.00 REF		
θ	0°		8°



Notes:

- (1) All dimensions are in millimeters. Angles in degrees.
- (2) Complies with JEDEC MO-153.

DOCUMENT NUMBER:	98AON34454E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TSSOP24, 4.4X7.8	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales